



# Silex Clarity SP3000

High-end portable USB and 5.8Ghz speakerphone



Silex Clarity SP3000 is a High-end 5.8G speakerphone. Ideal for small, medium, and large conference rooms and home offices, it can also be used as a personal portable device for online teachers, and business travelers. It brings the latest Sonic Clear IV high-definition voice processing technology thus providing crystal clear HD voice for music, calls and multimedia applications. With 4 integrated highly sensitive microphones insuring an omnidirectional pick-up pattern, laptop or tablet speakers and microphones will be instantly replaced for an ultimate sound quality and an increased voice pick up range. For users on the move, Silex Clarity SP3000 offers up to 4 hours of talk time.

## Main Features

- 4 Built-in high-sensitive microphones with 5m pick up range
- 22KHz full duplex
- 5.8G Wireless connection or USB Plug & Play
- Connects to laptop or smart devices
- Echo Cancellation and noise reduction
- Compatible with most videoconferencing software and cloud applications
- Portable with battery life for 4 hours talk time
- Can be connected to an external headphone or speakers
- 2 optional external microphones increase the pick-up range to 8m

# Specifications

## Built-in Speakerphone:

- Acoustic echo cancelation (AEC): >65dB
- Echo length cancellation: ≥500ms
- Bi-directional noise compression (NC): <25dB
- Automatic gain control (AGC)
- Frequency response : 100Hz-22KHz
- Volume : 95dB max

## Built-in Digital Microphone:

- 4 EMI microphones
- Automatic direction-finding technology of intelligence
- Frequency response: 100Hz-22KHz
- Pickup Range: 5m

## Expansion microphones (optional):

- 2 expansion microphones
- Increase the pick up range to 8m

## Connectivity:

- USB Type A
- Wifi 5.8G (using included wireless adapter)
- 3.5mm audio output
- RJ45 EX1, EX2
- I/O line in/out
- DIP6 interface

## System compatibility:

- Windows
- Mac OSX
- Android

**Power:** USB power supply: 5V/500m

## Weight and Dimensions:

- Size: 141×141mm×42mm
- Weight: 260g

## Temperature and Humidity:

- Working temperature: 0°C ~ 40°C
- Working humidity: 20-85% (no frost)





© 2021 SillexPro. All rights reserved. SillexPro and any SillexPro product or service name or logo used herein are trademarks of SillexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SillexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SillexPro.

[www.Sillexpro.com](http://www.Sillexpro.com)