

Silex EdTech AT12

Intelligent auto-tracking camera for education



Silex EdTech AT12 is a high-definition intelligent auto-tracking camera specially designed for education environments.

For small to medium classrooms or training rooms, this compact camera is built-in with a 12x optical zoom, high-speed processor, advanced image processing and analysis algorithms to track the lecturer quickly and accurately - a major requirements for remote interactive teaching. With its step driving motor mechanism and strong anti-interference ability, Silex EdTech AT12 locks its target, is extremely quiet and moves smoothly offering an excellent auto-tracking experience.

Auto-tracking features

- Built-in reference panoramic camera: Insures an optimal fusion between the reference camera and the tracking camera
- Advanced tracking algorithms: Advanced human presence detection, locking and tracking
- Analysis algorithm: Ensures the tracking is steady, accurate, fast and silent
- Strong anti-interference ability: once the tracking target is locked, it is not affected by other moving objects, projectors...
- Smooth tracking: The sensitivity to movement can be adjusted. Small movements or gestures will not trigger the camera to move unnecessarily
- Auto adaptation: Depending on the tracked target's location in the room, the tracking camera will automatically zoom keeping the video image in the appropriate size and proportions
- Ultra-wide dynamic exposure: Solves the challenge of the tracking target darkening when moving in front of a projector's light.

Specifications

Tracking Camera:

- Camera sensor: 1/2.8" CMOS
- Effective pixel: 2.07 Megapixel
- Ratio: 16:9
- Lens focus: 3.9mm~46.1mm
- Optical zoom: 12x optical zoom
- Digital zoom: 10x
- View angle: 6.3° (tele) ~72.5° (wide)
- Iris: F1.8 ~ F2.4
- Video output format: 1080P60, 1080I60, 720P60
- White balance: Manual/Auto/One Push/3000K/4000K/5000K/6500K
- Focus: Auto/Manual
- Aperture: Auto/Manual
- Electronic shutter: Auto/Manual
- BLC: ON/OFF
- WDR: OFF/Dynamic range adjustment
- Video adjustment: Brightness, Color, Saturation, contrast, Sharpness, Gamma curve
- SNR: >55db

Scene Camera:

- Camera sensor: 1/3" CMOS
- Effective pixel: 2.1 Megapixel
- Lens focus: Manual
- View angle (D/H/V): 90°/71°/52°

Pan Tilt Parameters:

- Pan rotation: -170° ~ +170°
- Tilt rotation: -30° ~ +90°
- Pan control speed: 0.1° ~ 100°/s
- Tilt control speed: 0.1° ~ 45°/s
- Preset speed: Pan: 100°/s, Tilt: 45°/s
- Number of presets: up to 255 presets (10 presets from remote control)

Input/Output Interface and Protocols:

- Video interface: HDMI, USB 3.0
- Network interface: 100M network interface (10/100BASE-TX) – 5G WiFi (optional)
- Network protocol: RTSP, RTMP, ONVIF, GB/T28181
- Compress image code stream: Dual stream output
- Video compress format: H.264, H.265
- Control signal interface: RS-232
- Control Protocol: Visca/Pelco-D/ Pelco-P Baud rate: 115200/9600/4800/2400bps
- Audio input interface: Dual Audio channel 3.5mm linear input
- Audio compress format: AAC, MP3, PCM
- Power interface: HEC3800 power jacket (DC12V)

Power:

- Consumption: 18W Max
- Power adapter: Input AC110V-AC220V to DC12V/2.5A
- Input voltage: Output DC12V +- 10%
- POE power supply (optional)
- Input current: 1.5A Max

Weight and Dimensions:

- Dimension (WxHxW): 254mm×144mm×174mm
- Weight: 1.5 Kg

Temperature and humidity:

- Working temperature: -10°C ~ 50°C
- Storage temperature: -10°C ~ 60°C
- Working humidity: 20-80%
- Storage humidity: 20-95%



© 2021 SillexPro. All rights reserved. SillexPro and any SillexPro product or service name or logo used herein are trademarks of SillexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SillexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SillexPro.

www.Sillexpro.com