



Silex Eye-Clarity DZ4

EPTZ Ultra HD auto framing camera



Silex Eye-Clarity DZ4 is a professional 4K Ultra HD video conferencing camera with two embedded high sensitivity microphones. It is an ideal Plug & Play camera that connects to a laptop via USB for personal use, or for huddle rooms and small to medium conference rooms.

Easy to install and operate with most video conferencing software the Eye-Clarity DZ4 can be remote controlled and offers a wide field of view with auto framing and ePTZ for an optimal video experience.

Main Features

- 4K Ultra HD image sensor with 8.42MP optical full glass lens for crisp images
- Two built-in high-sensitivity omni-directional digital microphones
- 120° Ultra-wide Angle
- Auto-framing
- ePTZ function with 4x lossless digital zoom and electronic pan/tilt
- USB Plug & Play
- Supports image flip for upside down ceiling installation
- Remote control
- 3 camera preset positions

Specifications

Camera:

- Camera sensor: 1/2.8" high quality 8.42MP CMOS
- Effective pixel: 8.42 Megapixel
- Minimum illumination: 0.1Lux at F2.0
- Noise reduction : 3D
- White Balance : Auto
- Anti-Flicker: Off / 50Hz / 60Hz
- Gain control : Auto
- Backlight compensation
- Electronic Shutter: auto / Manual
- SNR : >50db
- Lens focus: f=2.22mm F2.0
- 3 camera preset positions using the remote control
- Zoom: Fixed Lens with E-PTZ, 4x digital zoom
- Pan/Tilt: electronic
- Horizontal FOV: 120°
- Video output interface: USB2.0
- Mirror: supported
- Ceiling mount: supported
- Image flip: supported
- Video output format:
 - MJPG/H.264/H.265:
3840*2160@30,
2560*1440@30,
1920*1080@30, 1280*720@
30, 640*480@30, 320*240@30
 - YUY2/NV12: 1920*1080@30,
1280*720@30, 640x480@30,
320*240@30

Built-in Microphones:

- 2x high sensitivity omni-directional
- Pickup Range: 5m

Power supply: USB 2.0 5V 1A

Weight and Dimensions:

- Dimension: 199 × 93 × 65mm
- Weight: 370g

Temperature and Humidity:

- Working temperature: -10°C ~ 50°C
- Storage temperature: -20°C ~ 60°C
- Working humidity: 10% ~ 80%
- Storage humidity: 0% ~ 95%



© 2021 SillexPro. All rights reserved. SillexPro and any SillexPro product or service name or logo used herein are trademarks of SillexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SillexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SillexPro.

www.Sillexpro.com